



IPC-2152

Standard for Determining Current Carrying Capacity in Printed Board Design

August 2009

A standard developed by IPC

Association Connecting Electronics Industries



This is a preview. [Click here to purchase the full publication.](#)

The Principles of Standardization

In May 1995 the IPC's Technical Activities Executive Committee (TAEC) adopted Principles of Standardization as a guiding principle of IPC's standardization efforts.

Standards Should:

- Show relationship to Design for Manufacturability (DFM) and Design for the Environment (DFE)
- Minimize time to market
- Contain simple (simplified) language
- Just include spec information
- Focus on end product performance
- Include a feedback system on use and problems for future improvement

Standards Should Not:

- Inhibit innovation
- Increase time-to-market
- Keep people out
- Increase cycle time
- Tell you how to make something
- Contain anything that cannot be defended with data

Notice

IPC Standards and Publications are designed to serve the public interest through eliminating misunderstandings between manufacturers and purchasers, facilitating interchangeability and improvement of products, and assisting the purchaser in selecting and obtaining with minimum delay the proper product for his particular need. Existence of such Standards and Publications shall not in any respect preclude any member or nonmember of IPC from manufacturing or selling products not conforming to such Standards and Publication, nor shall the existence of such Standards and Publications preclude their voluntary use by those other than IPC members, whether the standard is to be used either domestically or internationally.

Recommended Standards and Publications are adopted by IPC without regard to whether their adoption may involve patents on articles, materials, or processes. By such action, IPC does not assume any liability to any patent owner, nor do they assume any obligation whatever to parties adopting the Recommended Standard or Publication. Users are also wholly responsible for protecting themselves against all claims of liabilities for patent infringement.

IPC Position Statement on Specification Revision Change

It is the position of IPC's Technical Activities Executive Committee that the use and implementation of IPC publications is voluntary and is part of a relationship entered into by customer and supplier. When an IPC publication is updated and a new revision is published, it is the opinion of the TAEC that the use of the new revision as part of an existing relationship is not automatic unless required by the contract. The TAEC recommends the use of the latest revision. Adopted October 6, 1998

Why is there a charge for this document?

Your purchase of this document contributes to the ongoing development of new and updated industry standards and publications. Standards allow manufacturers, customers, and suppliers to understand one another better. Standards allow manufacturers greater efficiencies when they can set up their processes to meet industry standards, allowing them to offer their customers lower costs.

IPC spends hundreds of thousands of dollars annually to support IPC's volunteers in the standards and publications development process. There are many rounds of drafts sent out for review and the committees spend hundreds of hours in review and development. IPC's staff attends and participates in committee activities, typesets and circulates document drafts, and follows all necessary procedures to qualify for ANSI approval.

IPC's membership dues have been kept low to allow as many companies as possible to participate. Therefore, the standards and publications revenue is necessary to complement dues revenue. The price schedule offers a 50% discount to IPC members. If your company buys IPC standards and publications, why not take advantage of this and the many other benefits of IPC membership as well? For more information on membership in IPC, please visit www.ipc.org or call 847/597-2872.

Thank you for your continued support.



IPC-2152

Standard for Determining Current Carrying Capacity in Printed Board Design

Developed by the Current Carrying Capacity Task Group (1-10b) of the Printed Board Design Committee (1-10) of IPC

Users of this standard are encouraged to participate in the development of future revisions.

Contact:

IPC
3000 Lakeside Drive, Suite 309S
Bannockburn, Illinois
60015-1249
Tel 847 615.7100
Fax 847 615.7105

This is a preview. [Click here to purchase the full publication.](#)

This Page Intentionally Left Blank

Acknowledgment

Any document involving a complex technology draws material from a vast number of sources. While the principal members of the Current Carrying Capacity Task Group (1-10b) of the Printed Board Design Committee (1-10) are shown below, it is not possible to include all of those who assisted in the evolution of this standard. To each of them, the members of the IPC extend their gratitude.

Printed Board Design Committee

Chair
Lionel Fullwood
WKK Distribution Ltd.

Vice Chair
Gary Ferrari
FTG Circuits

Current Carrying Capacity Task Group

Chair
Michael Jouppi
Lockheed Martin

Technical Liaisons of the IPC Board of Directors

Peter Bigelow
IMI Inc.

Sammy Yi
Aptina Imaging Corporation

Current Carrying Capacity Task Group

Byron Case, L-3 Communications
Phillip Chen, L-3 Communications
Electronic Systems
David Corbett, Defense Supply
Center Columbus
William Dieffenbacher, BAE Systems
Platform Solutions
C. Don Dupriest, Lockheed Martin
Missiles and Fire Control
Gary Ferrari, FTG Circuits

Lionel Fullwood, WKK Distribution
Ltd.
Michael Green, Lockheed Martin
Space Systems Company
Christopher Katzko, Shanghai
Meadville Electronics Co. Ltd.
Donald Kyle, Schlumberger Well
Services
Jim Long, ITT Power Solutions
Kenneth Manning, Raytheon
Company

Michael Miller, NSWC Crane
Tim Minko, Coretec Inc.
Gary Morgan, Ball Aerospace &
Technologies
Jack Olson, Caterpillar Inc.
William Ortloff, Raytheon Company
Karl Sauter, Sun Microsystems Inc.
Dewey Whittaker, Honeywell Inc. Air
Transport Systems
John Williams, Raytheon Company

A special note of thanks goes to the following individuals for their dedication to bringing this project to fruition. We would like to highlight those individuals who made major contributions to the development of this standard.

C. Don Dupriest, Lockheed Martin
Missiles and Fire Control
Michael Green, Lockheed Martin
Space Systems Company

Michael Jouppi, Lockheed Martin
Jack Olson, Caterpillar Inc.
Michael Miller, NSWC Crane

Brian Strandjord, Thermal
Management, Inc.

This Page Intentionally Left Blank

Table of Contents

1 SCOPE	1	A.3.3 Parallel Conductors.....	20
1.1 Purpose	1	A.3.4 Vias.....	26
1.2 Presentation	1	A.3.4.1 Conductor to Via to Plane.....	26
1.3 Interpretation	1	A.3.4.2 Microvia	26
1.4 Definition of Terms	1	A.4 SUPPLEMENTAL MATERIAL	27
1.4.1 Ambient	1	A.4.1 Flex Circuits.....	27
1.4.2 Base Material	1	A.4.2 PB Thickness	27
1.4.3 Circuitry Layer	1	A.4.3 Copper Weight	28
1.4.4 Conductive Pattern	1	A.4.4 Board Material	29
1.4.5 Conductor Spacing	1	A.4.5 Environments	29
1.4.6 Conductor Thickness	1	A.4.6 Copper Planes	29
1.4.7 Conductor Width	1	A.4.6.1 Single Plane	29
1.4.8 Convection	1	A.4.6.2 Conductor Distance from Plane	30
1.4.9 Copper Weight	1	A.5 ADDITIONAL TOPICS	31
1.4.10 Current-Carrying Capacity	1	A.5.1 Heat Transfer from a Conductor.....	31
1.4.11 Heat Sink Plane	2	A.5.2 Conductor Power Dissipation.....	31
1.4.12 Thermal Conductivity	2	A.5.2.1 Conductor Electrical Resistance.....	31
1.4.13 Thermal Resistance	2	A.5.3 Odd Shaped Geometries and Swiss-Cheese Effect	32
2 APPLICABLE DOCUMENTS	2	A.5.3.1 Voltage Drop Analysis.....	32
2.1 IPC	2	A.5.3.2 Voltage Sources.....	32
3 CONDUCTOR SIZING INTRODUCTION	2	A.5.3.3 Current Source (or Sink).....	32
4 CONDUCTOR SIZING DESIGN GUIDELINES	2	A.5.3.4 Electrical Conductivity	32
5 CONDUCTOR SIZING CHARTS	3	A.5.4 HDI.....	33
5.1 Conductor Sizing Charts for Still Air Environments	6	A.5.5 High-Speed.....	33
5.1.1 Still Air Environment Charts in Imperial (Inch) Units	6	A.6 CONDUCTOR SIZING CHARTS	33
5.1.2 Still Air Environment Charts in SI (Metric) Units	9	A.6.1 Conductor Sizing Charts for Still Air Environments	33
5.2 Conductor Sizing Charts for Vacuum/Space Environments	12	A.6.1.1 Still Air Environment Charts in Imperial (Inch) Units.....	34
5.2.1 Vacuum/Space Environment Charts in Imperial (Inch) Units	12	A.6.1.2 Still Air Environment Charts in SI (Metric) Units	50
5.2.2 Vacuum/Space Environment Charts in SI (Metric) Units	15	A.6.2 Conductor Sizing Charts for Vacuum/Space Environments	68
APPENDIX A	18	A.6.2.1 Vacuum/Space Environment Charts in Imperial (Inch) Units	68
A.1 INTRODUCTION	18	A.6.2.2 Vacuum/Space Environment Charts in SI (Metric) Units	76
A.2 DERATING	18	A.7 REFERENCES	85
A.3 SELECTING A CHART	18	A.7.1 The Origin of the First Conductor Sizing Chart	85
A.3.1 Conductor Temperature Rise.....	20		
A.3.2 How to Use the Charts.....	20		
A.3.2.1 Chart Basics: Known Current	20		

Figures

Figure 5-1	Internal and External Conductors (All Environments)	5	Figure A-10	Two 2.03 mm [0.080 in] Conductors (25.4 mm [1.0 in] spacing) No amperage adjustment	26
Figure 5-2	Internal and External Conductors (Still Air) (5-700 Sq-mils)	6	Figure A-11	Via Cross-sectional Area	27
Figure 5-3	Internal and External Conductors (Still Air) (5-700 Sq-mils)	7	Figure A-12	Via Temperature Gradient	27
Figure 5-4	Internal and External Conductors (Still Air) (5-100 Sq-mils)	7	Figure A-13	Distance from Conductor to Copper Plane	30
Figure 5-5	Internal and External Conductors (Still Air) (5 - 50 Sq-mils)	8	Figure A-14	Single Conductor in a PB	31
Figure 5-6	Internal and External Conductors (Still Air) (0.001 - 0.5 Sq-mm)	9	Figure A-15	3 oz. External Conductors (Still Air) Log (5 - 700 Sq-mils)	34
Figure 5-7	Internal and External Conductors (Still Air) (0.001 - 0.5 Sq-mm)	10	Figure A-16	3 oz. External Conductors (Still Air) (5 - 700 Sq-mils)	35
Figure 5-8	Internal and External Conductors (Still Air) (0.001 - 0.1 Sq-mm)	10	Figure A-17	3 oz. External Conductors (Still Air) (5 - 100 Sq-mils)	35
Figure 5-9	Internal and External Conductors (Still Air) (0.001 - 0.03 Sq-mm)	11	Figure A-18	3 oz. External Conductors (Still Air) (5 - 50 Sq-mils)	36
Figure 5-10	Internal and External Conductors (Vacuum) (5 - 700 Sq-mils)	12	Figure A-19	3 oz. Internal Conductors (Still Air) Log (5 - 700 Sq-mils)	37
Figure 5-11	Internal and External Conductors (Vacuum) (5 - 700 Sq-mils)	13	Figure A-20	3 oz. Internal Conductors (Still Air) (5 - 700 Sq-mils)	38
Figure 5-12	Internal and External Conductors (Vacuum) (5 - 100 Sq-mils)	13	Figure A-21	3 oz. Internal Conductors (Still Air) (5 - 100 Sq-mils)	38
Figure 5-13	Internal and External Conductors (Vacuum) (5 - 50 Sq-mils)	14	Figure A-22	3 oz. Internal Conductors (Still Air) (5 - 50 Sq-mils)	39
Figure 5-14	Internal and External Conductors (Vacuum) (0.001 - 0.5 Sq-mm)	15	Figure A-23	2 oz. External Conductors (Still Air) Log (5 - 700 Sq-mils)	40
Figure 5-15	Internal and External Conductors (Vacuum) (0.001 - 0.5 Sq-mm)	16	Figure A-24	2 oz. External Conductors (Still Air) (5 - 700 Sq-mils)	41
Figure 5-16	Internal and External Conductors (Vacuum) (0.001 - 0.1 Sq-mm)	16	Figure A-25	2 oz. External Conductors (Still Air) (5 - 100 Sq-mils)	41
Figure 5-17	Internal and External Conductors (Vacuum) (0.001 - 0.03 Sq-mm)	17	Figure A-26	2 oz. External Conductors (Still Air) (5 - 50 Sq-mils)	42
Figure A-1	External and Internal Conductors (This figure is a duplicate of Figure 5-1 in IPC-2152)	19	Figure A-27	2 oz. Internal Conductors (Still Air) Log (5 - 700 Sq-mils)	43
Figure A-2	External and Internal Conductor Sizing Chart	21	Figure A-28	2 oz. Internal Conductors (Still Air) (5 - 700 Sq-mils)	44
Figure A-3	Parallel Conductors	22	Figure A-29	2 oz. Internal Conductors (Still Air) (5 - 100 Sq-mils)	44
Figure A-4	[0.010 in] wide (1-oz.) Conductor at 10 °C Temperature Gradient	23	Figure A-30	2 oz. Internal Conductors (Still Air) (5 - 50 Sq-mils)	45
Figure A-5	4.06 mm [0.160 in] Single Conductor	23	Figure A-31	1 oz. Internal Conductors (Still Air) Log (5 - 700 Sq-mils)	46
Figure A-6	Two 2.03 mm [0.080 in] conductors (2.54 mm [0.100 in] spacing) amperage adjusted for parallel conductor	24	Figure A-32	1 oz. Internal Conductors (Still Air) (5 - 700 Sq-mils)	46
Figure A-7	Two 2.03 mm [0.080 in] Conductors (2.54 mm [0.100 in] spacing) No amperage adjustment	24	Figure A-33	1 oz. Internal Conductors (Still Air) (5 - 100 Sq-mils)	47
Figure A-8	Two 2.03 mm [0.080 in] Conductors (12.7 mm [0.50 in] spacing) Amperage adjusted for Parallel Conductor	25	Figure A-34	1 oz. Internal Conductors (Still Air) (5 - 50 Sq-mils)	47
Figure A-9	Two 2.03 mm [0.080 in] Conductors (25.4 mm [1.0 in] spacing) Amperage adjusted for Parallel Conductor	25	Figure A-35	1/2 oz. Internal Conductors (Still Air) Log (5 - 700 Sq-mils)	48
			Figure A-36	1/2 oz. Internal Conductors (Still Air) (5 - 700 Sq-mils)	48
			Figure A-37	1/2 oz. Internal Conductors (Still Air) (5 - 100 Sq-mils)	49
			Figure A-38	1/2 oz. Internal Conductors (Still Air) (5 - 50 Sq-mils)	49
			Figure A-39	3 oz. External Conductors (Still Air) Log (0.001 - 0.5 Sq-mm)	50

Figure A-40	3 oz. External Conductors (Still Air) (0 - 0.5 Sq-mm)	51	Figure A-68	2 oz. Conductors (Vacuum) (5 - 700 Sq-mils)	72
Figure A-41	3 oz. External Conductors (Still Air) (0 - 0.1 Sq-mm)	51	Figure A-69	2 oz. Conductors (Vacuum) (5 - 100 Sq-mils)	72
Figure A-42	3 oz. External Conductors (Still Air) (0 - 0.03 Sq-mm)	52	Figure A-70	2 oz. Conductors (Vacuum) (5 - 50 Sq-mils)	73
Figure A-43	3 oz. Internal Conductors (Still Air) Log (0 - 700 Sq-mm)	53	Figure A-71	1/2 oz. Conductors (Vacuum) Log (5 - 700 Sq-mils)	74
Figure A-44	3 oz. Internal Conductors (Still Air) (0 - 0.5 Sq-mm)	54	Figure A-72	1/2 oz. Conductors (Vacuum) (5 - 700 Sq-mils)	74
Figure A-45	3 oz. Internal Conductors (Still Air) (0 - 0.1 Sq-mm)	54	Figure A-73	1/2 oz. Conductors (Vacuum) (5 - 100 Sq-mils)	75
Figure A-46	3 oz. Internal Conductors (Still Air) (0 - 0.03 Sq-mm)	55	Figure A-74	1/2 oz. Conductors (5 - 50 Sq-mils)	75
Figure A-47	2 oz. External Conductors (Still Air) Log (0.001 - 0.5 Sq-mm)	56	Figure A-75	3 oz. Conductors (Vacuum) Log (0.001 - 0.5 Sq-mm)	76
Figure A-48	2 oz. External Conductors (Still Air) (0.001 - 0.5 Sq-mm)	57	Figure A-76	3 oz. Conductors (Vacuum) (0 - 0.5 Sq-mm)	77
Figure A-49	2 oz. External Conductors (Still Air) (0 - 0.1 Sq-mm)	57	Figure A-77	3 oz. Conductors (Vacuum) (0 - 0.1 Sq-mm)	77
Figure A-50	2 oz. External Conductors (Still Air) (0 - 0.03 Sq-mm)	58	Figure A-78	3 oz. Conductors (Vacuum) (0 - 0.03 Sq-mm)	78
Figure A-51	2 oz. Internal Conductors (Still Air) Log (0 - 0.5 Sq-mm)	59	Figure A-79	2 oz. Conductors (Vacuum) Log (0 - 0.5 Sq-mm)	79
Figure A-52	2 oz. Internal Conductors (Still Air) (0 - 0.5 Sq-mm)	60	Figure A-80	2 oz. Conductors (Vacuum) (0 - 0.5 Sq-mm)	80
Figure A-53	2 oz. Internal Conductors (Still Air) (0 - 0.1 Sq-mm)	60	Figure A-81	2 oz. Conductors (Vacuum) (0 - 0.1 Sq-mm)	80
Figure A-54	2 oz. Internal Conductors (Still Air) (0 - 0.03 Sq-mm)	61	Figure A-82	2 oz. Conductors (Vacuum) (0 - 0.03 Sq-mm)	81
Figure A-55	1 oz. Internal Conductors (Still Air) Log (0 - 0.1 Sq-mm)	62	Figure A-83	1/2 oz. Conductors (Vacuum) Log (0 - 0.5 Sq-mm)	82
Figure A-56	1 oz. Internal Conductors (Still Air) (0 - 0.5 Sq-mm)	62	Figure A-84	1/2 oz. Conductors (Vacuum) (0 - 0.5 Sq-mm)	82
Figure A-57	1 oz. Internal Conductors (Still Air) (0 - 0.1 Sq-mm)	63	Figure A-85	1/2 oz. Conductors (Vacuum) (0 - 0.1 Sq-mm)	83
Figure A-58	1 oz. Internal Conductors (Still Air) (0 - 0.03 Sq-mm)	64	Figure A-86	1/2 oz. Conductors (Vacuum) (0 - 0.03 Sq-mm)	83
Figure A-59	1/2 oz. Internal Conductors (Still Air) Log (0 - 0.5 Sq-mm)	65	Figure A-87	Log width chart	84
Figure A-60	1/2 oz. Internal Conductors (Still Air) (0 - 0.5 Sq-mm)	65	Figure A-88	Log width chart (inch)	84
Figure A-61	1/2 oz. Internal Conductors (Still Air) (0 - 0.1 Sq-mm)	66	Figure A-89	Original NBS Chart	86
Figure A-62	1/2 oz. Internal Conductors (Still Air) (0 - 0.03 Sq-mm)	67	Figure A-90	NBS 10 °C Data Curves	87
Figure A-63	3 oz. Conductors (Vacuum) Log (5 - 700 Sq-mils)	68	Figure A-91	Historical IPC Charts	88
Figure A-64	3 oz. Conductors (Vacuum) (0 - 700 Sq-mils)	69	Tables		
Figure A-65	3 oz. Conductors (Vacuum) (0 - 100 Sq-mils)	69	Table A-1	Minimum Internal Copper Foil Thickness (For Reference Only)	28
Figure A-66	3 oz. Conductors (Vacuum) (5 - 50 Sq-mils)	70	Table A-2	Minimum External Conductor Thickness (For Reference Only)	28
Figure A-67	2 oz. Conductors (Vacuum) Log (5 - 700 Sq-mils)	71	Table A-3	Material Thermal Conductivity	29
			Table A-4	Skin Depth Parameters	33
			Table A-5	NBS Data Reference Table	89
			Table A-6	NBS Data Reference Table (Cont'd)	89
			Table A-7	NBS Data Reference Table (Cont'd)	89

This Page Intentionally Left Blank