
Road vehicles — Automotive cables —
Part 8:
Dimensions and requirements for
30 V a.c. or 60 V d.c. round, sheathed,
screened or unscreened multi or single
core aluminium conductor cables

Véhicules routiers — Câbles automobiles —

Partie 8: Dimensions et exigences des câbles en aluminium ronds, gainés, blindés, à plusieurs ou unique noyau blindés 30 V a.c ou 60 V c.c.





COPYRIGHT PROTECTED DOCUMENT

© ISO 2019

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Fax: +41 22 749 09 47
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

	Page
Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Specifications	1
4.1 General test conditions.....	1
4.2 Safety concerns.....	2
4.3 Voltage rating.....	2
4.4 Temperature classes.....	2
4.5 Conductor material.....	2
4.6 Conductors.....	2
4.7 Sheath thickness.....	2
4.8 Core cable outside diameter.....	2
4.9 Representative conductor sizes for testing.....	2
4.10 Reference and requirements for the tests according to ISO 19642-2.....	3
5 Requirements for single core cables	5
6 Requirements for round, sheathed, screened or unscreened multi or single core cables	5
6.1 General.....	5
6.2 Dimensional tests.....	5
6.2.1 Cable outside and inner layer diameters.....	5
6.2.2 Ovality of sheath.....	6
6.2.3 Thickness of sheath.....	6
6.2.4 In-process cable outside diameter.....	6
6.3 Electrical tests.....	6
6.3.1 Electrical continuity.....	6
6.3.2 Withstand voltage at final inspection.....	6
6.3.3 Screening effectiveness.....	6
6.3.4 Sheath fault on screened cables.....	7
6.4 Mechanical tests.....	7
6.4.1 Strip force of sheath.....	7
6.4.2 Cyclic bending.....	7
6.4.3 Flexibility.....	7
6.5 Environmental tests.....	7
6.5.1 Test specimen preparation and winding tests.....	7
6.5.2 Long term heat ageing, 3 000 h at temperature class rating.....	7
6.5.3 Short term heat ageing, 240 h at temperature class rating +25 °C.....	7
6.5.4 Thermal overload, 6 h at temperature class rating +50 °C.....	7
6.5.5 Pressure test at high temperature.....	8
6.5.6 Shrinkage by heat of sheath.....	8
6.5.7 Low temperature winding.....	8
6.5.8 Cold impact.....	8
6.5.9 Temperature and humidity cycling.....	8
6.5.10 Resistance to liquid chemicals.....	8
6.5.11 Durability of sheath marking.....	8
6.5.12 Resistance to ozone.....	8
6.5.13 Artificial weathering.....	8
6.5.14 Resistance to flame propagation.....	9
Annex A (informative) Dimensions of preferred constructions	10
Bibliography	16