

UL 1429

STANDARD FOR SAFETY

Pullout Switches



UL Standard for Safety for Pullout Switches, UL 1429

Fourth Edition, Dated April 18, 2000

SUMMARY OF TOPICS

This revision of ANSI/UL 1429 dated December 4, 2020 includes the following changes:

Barriers to address inadvertent contact on line side of service disconnect; Section <u>18A</u>, Table 49.1 and 49.5.7.

Editorial updates; 9.2, 11.2.1, 11.2.2, 17.2, 20.5, 26.3, and 37.2.

Text that has been changed in any manner or impacted by UL's electronic publishing system is marked with a vertical line in the margin.

These new and revised requirements are substantially in accordance with Proposal (s) on this subject dated August 28, 2020.

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system, or transmitted in any form by any means, electronic, mechanical photocopying, recording, or otherwise without prior permission of UL.

UL provides this Standard "as is" without warranty of any kind, either expressed or implied, including but not limited to, the implied warranties of merchantability or fitness for any purpose.

In no event will UL be liable for any special, incidental, consequential, indirect or similar damages, including loss of profits, lost savings, loss of data, or any other damages arising out of the use of or the inability to use this Standard, even if UL or an authorized UL representative has been advised of the possibility of such damage. In no event shall UL's liability for any damage ever exceed the price paid for this Standard, regardless of the form of the claim.

Users of the electronic versions of UL's Standards for Safety agree to defend, indemnify, and hold UL harmless from and against any loss, expense, liability, damage, claim, or judgment (including reasonable attorney's fees) resulting from any error or deviation introduced while purchaser is storing an electronic Standard on the purchaser's computer system.

No Text on This Page

APRIL 18, 2000

(Title Page Reprinted: December 4, 2020)



1

UL 1429

Standard for Pullout Switches

First Edition – December, 1985 Second Edition – October, 1988 Third Edition – October, 1994

Fourth Edition

April 18, 2000

This ANSI/UL Standard for Safety consists of the Fourth edition including revisions through December 4, 2020.

The most recent designation of ANSI/UL 1429 as an American National Standard (ANSI) occurred on December 4, 2020. ANSI approval for a standard does not include the Cover Page, Transmittal Pages, and Title Page.

Comments or proposals for revisions on any part of the Standard may be submitted to UL at any time. Proposals should be submitted via a Proposal Request in UL's On-Line Collaborative Standards Development System (CSDS) at https://csds.ul.com.

UL's Standards for Safety are copyrighted by UL. Neither a printed nor electronic copy of a Standard should be altered in any way. All of UL's Standards and all copyrights, ownerships, and rights regarding those Standards shall remain the sole and exclusive property of UL.

COPYRIGHT © 2020 UNDERWRITERS LABORATORIES INC.

This is a preview. Click here to purchase the full publication.

No Text on This Page

CONTENTS

34

INTRODUCTION		
1	Scope	5
2	Components	
3	Units of Measurement	
4	References	
7	TKGIGIGIGGS	0
CONST	RUCTION	
5	General	
6	Enclosure	7
	6.1 General	7
	6.2 Doors and covers	
7	Bases – Insulating Material	8
8	Operating Mechanism	8
9	Disconnecting Means	12
10	Overcurrent Protection	13
11	Current-Carrying Parts	13
	11.1 General	13
	11.2 Wiring terminals	15
12	Equipment Grounding Terminals	17
13	Field Conversion	19
14	Spacings	20
15	Insulating Barriers	
16	Wiring Space	
17	Wire Bending Space	
18	Provision for Bonding for Enclosed Pullout Switches	
18/		
PERFO	RMANCE	
10	General	24
19		
20	Heating Test	
21	Heating With Fuses Test	
	21.1 30 and 60 A Class H fuses	
00	21.2 Class CC, G, J, and R fuses	
22	Overload-Cycle-Heating Test	
23	Overload Test	
24	Endurance Test	
25	Dielectric Voltage-Withstand Test	
26	Short-Circuit Withstand Test	
27	Low Level Dielectric Voltage-Withstand Test	
28	Closing Test	43
29	Low Level Dielectric Voltage-Withstand Test	
30	Test Calibration	
31	Strength of Insulating Base and Support Test	
32	Bonding Continuity Test	
33	Clamped Joint Test	43
PERFO	RMANCE – HIGHER THAN 10 KA AVAILABLE FAULT CURRENT CIRCUITS	